

# RLL

Radial Lead Type  
series

Super low ESR, High ripple current  
Large capacitance, Small size  
Load life of 5,000h at 105°C



## ● Specifications

Items	Characteristics	
Temperature range	-55 to +105°C	
Rated voltage range	2.5 to 16Vdc	
Capacitance range	100 to 3,500μF	
Capacitance tolerance	±20% [M] (at 20°C, 120Hz)	
Tangent of loss angle	Less than or equal to the value of Standard Ratings (at 20°C, 120Hz)	
Leakage current	Less than or equal to the value of Standard Ratings (at 20°C, after 2 minutes)	
ESR	Less than or equal to the value of Standard Ratings	
Characteristics of impedance	$Z_{+105^\circ\text{C}}/Z_{+20^\circ\text{C}} \leq 1.25$ , $Z_{-55^\circ\text{C}}/Z_{+20^\circ\text{C}} \leq 1.25$ at 100kHz	
Endurance	105°C, 5,000 hrs at rated voltage	
	Appearance	No significant damage
	Capacitance change	Within±20% of the initial value
	Tangent of loss angle (tanδ)	≤150% of the initial specified value
	ESR(mΩ)	≤150% of the initial specified value
	Leakage current	≤The initial specified value
Damp Heat (Steady State)	60°C, 90 to 95% RH, 1,000 hrs, No-applied Voltage	
	Appearance	No significant damage
	Capacitance change	Within±20% of the initial value
	Tangent of loss angle (tanδ)	≤150% of the initial specified value
	ESR(mΩ)	≤150% of the initial specified value
	Leakage current	≤The initial specified value
Resistance to soldering heat	Flow method (260±5°C, 10s)	
	Appearance	No significant damage
	Capacitance change	Within±10% of the initial value
	Tangent of loss angle (tanδ)	≤130% of the initial specified value
	ESR(mΩ)	≤130% of the initial specified value
	Leakage current	≤The initial specified value

\* In case of some problems for measured values, measure after applying rated voltage for 120 minutes at 105°C

## ● Size List

(unit: mm)

$\mu\text{F}$	RV (SV) (2.5) (2.9)	4 (4.6)	6.3 (7.2)	10 (11.5)	16 (18.4)	
100					6.3x6 / 6.3x9	
150				6.3x6	8x7	
180					8x9 / 8x11.5	
220	5x9		6.3x6		8x7	
270				8x7	6.3x9 / 8x9 8x11.5	
330	5x9 6.3x9			8x7	8x9 / 8x11.5 10x11.5	
470	5x9		6.3x9 / 8x9 8x11.5		10x11.5	
560	5x9 / 6.3x9 8x9	6.3x9 / 8x9 8x11.5	6.3x9 8x9			
680		8x11.5	10x11.5	8x9		
820	6.3x9 / 8x7 8x9 / 8x11.5	10x11.5	8x9 8x11.5			
1000	8x9	8x9 10x11.5	8x9	8x11.5	10x11.5	
1200		8x9	8x11.5	10x11.5		
1500	8x9		10x11.5			
2700	10x11.5					
3500	10x11.5					

RV: Rated Voltage [V] SV: Surge Voltage [V] (at room temperature)

## ● Marking and Dimensions

	Date Code																																																						
	Series																																																						
	Rated capacitance [ $\mu\text{F}$ ]																																																						
	Rated voltage [V]																																																						
	(unit: mm)																																																						
<table border="1"> <thead> <tr> <th>Size</th> <th><math>\text{ØD} \pm 0.5</math></th> <th>L</th> <th>L'</th> <th>P <math>\pm 0.5</math></th> <th><math>\text{Ød}</math></th> </tr> </thead> <tbody> <tr> <td>5x9</td> <td>5.0</td> <td>9.0</td> <td></td> <td>2.0</td> <td>0.6</td> </tr> <tr> <td>6.3x6</td> <td>6.3</td> <td>6.0</td> <td></td> <td>2.5</td> <td>0.45</td> </tr> <tr> <td>8x7</td> <td>8.0</td> <td>7.0</td> <td></td> <td>3.5</td> <td>0.45</td> </tr> <tr> <td>6.3x9</td> <td>6.3</td> <td>9.0</td> <td></td> <td>2.5</td> <td>0.6</td> </tr> <tr> <td>8x9</td> <td>8.0</td> <td>9.0</td> <td></td> <td>3.5</td> <td>0.6</td> </tr> <tr> <td>8x11.5</td> <td>8.0</td> <td>11.5</td> <td></td> <td>3.5</td> <td>0.6</td> </tr> <tr> <td>10x11.5</td> <td>10.0</td> <td>11.5</td> <td></td> <td>L + 1.0 max.</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>5.0</td> <td>0.6</td> </tr> </tbody> </table>	Size	$\text{ØD} \pm 0.5$	L	L'	P $\pm 0.5$	$\text{Ød}$	5x9	5.0	9.0		2.0	0.6	6.3x6	6.3	6.0		2.5	0.45	8x7	8.0	7.0		3.5	0.45	6.3x9	6.3	9.0		2.5	0.6	8x9	8.0	9.0		3.5	0.6	8x11.5	8.0	11.5		3.5	0.6	10x11.5	10.0	11.5		L + 1.0 max.						5.0	0.6	
Size	$\text{ØD} \pm 0.5$	L	L'	P $\pm 0.5$	$\text{Ød}$																																																		
5x9	5.0	9.0		2.0	0.6																																																		
6.3x6	6.3	6.0		2.5	0.45																																																		
8x7	8.0	7.0		3.5	0.45																																																		
6.3x9	6.3	9.0		2.5	0.6																																																		
8x9	8.0	9.0		3.5	0.6																																																		
8x11.5	8.0	11.5		3.5	0.6																																																		
10x11.5	10.0	11.5		L + 1.0 max.																																																			
				5.0	0.6																																																		

## ● Standard Ratings

Rated Voltage [Vdc]	Rated Capacitance [ $\mu$ F]	Size ØD x L [mm]	ESR (20°C, 100kHz) [mΩ] [max.]	Rated Ripple Current (105°C, 100kHz) [mArms]	Tangent of Loss Angel [max.]	Leakage Current [ $\mu$ A, max.]	Part Number
2.5	220	5 x 9	7	4180	0.10	500	2RLL220MB9
	330	5 x 9	7	4180	0.10	500	2RLL330MB9
	330	6.3 x 9	7	5600	0.10	500	2RLL330MC9
	470	5 x 9	7	4180	0.10	500	2RLL470MB9
	560	5 x 9	7	4180	0.10	500	2RLL560MB9
	560	6.3 x 9	7	5600	0.10	500	2RLL560MC9
	560	8 x 9	7	6100	0.10	500	2RLL560MD9
	820	6.3 x 9	7	5600	0.10	500	2RLL820MC9
	820	8 x 7	8	5300	0.10	500	2RLL820MD7
	820	8 x 9	7	6100	0.10	500	2RLL820MD9
	820	8 x 11.5	7	6100	0.10	500	2RLL820MD11
	1000	8 x 9	7	6100	0.10	500	2RLL1000MD9
	1500	8 x 9	7	6100	0.10	750	2RLL1500MD9
	2700	10 x 11.5	10	5560	0.10	1350	2RLL2700ME11
	3500	10 x 11.5	10	5560	0.10	1750	2RLL3500ME11
4	560	6.3 x 9	7	5600	0.10	500	4RLL560MC9
	560	8 x 9	7	6100	0.10	500	4RLL560MD9
	560	8 x 11.5	7	6100	0.10	500	4RLL560MD11
	680	8 x 11.5	7	6100	0.10	544	4RLL680MD11
	820	10 x 11.5	7	6640	0.10	656	4RLL820ME11
	1000	8 x 9	7	6100	0.10	800	4RLL1000MD9
	1000	10 x 11.5	7	6640	0.10	800	4RLL1000ME11
	1200	8 x 9	7	6100	0.10	960	4RLL1200MD9
	220	6.3 x 6	18	2980	0.10	277	6RLL220MC6
	470	6.3 x 9	7	5600	0.10	592	6RLL470MC9
6.3	470	8 x 9	7	5700	0.10	592	6RLL470MD9
	470	8 x 11.5	7	5700	0.10	592	6RLL470MD11
	560	6.3 x 9	7	5600	0.10	705	6RLL560MC9
	560	8 x 9	7	5700	0.10	705	6RLL560MD9
	680	10 x 11.5	7	6640	0.10	857	6RLL680ME11
	820	8 x 9	7	5700	0.10	1033	6RLL820MD9
	820	8 x 11.5	7	5700	0.10	1033	6RLL820MD11
	1000	8 x 9	7	5700	0.10	1260	6RLL1000MD9
	1200	8 x 11.5	7	5700	0.10	1512	6RLL1000MD11
	1500	10 x 11.5	10	5560	0.10	1890	6RLL1500ME11
	150	6.3 x 6	26	2400	0.10	300	10RLL150MC6
	270	8 x 7	22	3220	0.10	500	10RLL270MD7
10	330	8 x 7	22	3390	0.10	500	10RLL330MD7
	680	8 x 9	9	5600	0.10	1360	10RLL680MC9
	1000	8 x 11.5	10	6100	0.10	2000	10RLL1000MD11
	1200	10 x 11.5	8	6100	0.10	2400	10RLL1200ME11
	100	6.3 x 6	24	2490	0.10	320	16RLL100MC6
	100	6.3 x 9	10	4680	0.10	500	16RLL100MC9
16	150	8 x 7	22	3220	0.10	500	16RLL150MD7
	180	8 x 9	10	5000	0.10	576	16RLL180MD9
	180	8 x 11.5	16	4360	0.10	576	16RLL180MD11
	220	8 x 7	13	4150	0.10	704	16RLL220MD7
	270	6.3 x 9	10	4680	0.10	864	16RLL270MC9
	270	8 x 9	10	5000	0.10	864	16RLL270MD9
	270	8 x 11.5	11	5000	0.10	864	16RLL270MD11
	330	8 x 9	11	4520	0.10	1056	16RLL330MD9
	330	8 x 11.5	11	5000	0.10	1056	16RLL330MD11
	330	10 x 11.5	8	6000	0.10	1056	16RLL330ME11
	470	10 x 11.5	10	6100	0.10	1504	16RLL470ME11
	1000	10 x 11.5	10	6100	0.10	3200	16RLL1000ME11

Conductive Polymer Hybrid  
Aluminum Electrolytic Capacitors  
Radial Lead Type

Conductive Polymer Hybrid  
Aluminum Electrolytic Capacitors  
SMD Lead Type

Conductive Polymer Aluminum  
Electrolytic Capacitors\_Radial Lead Type

Conductive Polymer Aluminum  
Electrolytic Capacitors\_SMD Lead Type